

Project Name: **454B Stock**

Unit Model #: **KC120C00A2AAA1**

Quantity: **1**

System: **KC120C00A2AAA1, GL120C00C2BAA1**

Cooling Performance

Total gross capacity	127.0 MBH
Sensible gross capacity	91.8 MBH
Efficiency (at ARI)	11.20 EER
Integrated eff. (at ARI)	15.50 IEER
Ambient DB temp.	95.0 °F
Entering DB temp.	80.0 °F
Entering WB temp.	67.0 °F
Evap Coil Leaving DB temp.	58.8 °F
Evap Coil Leaving WB temp.	56.9 °F
Unit Leaving DB temp.	60.0 °F
Unit Leaving WB temp.	57.4 °F
Leaving air temp dew point	55.70 °F
Power input (w/o blower)	9.10 kW
Sound power	90 dB(a)

Refrigerant

Refrigerant type	R-454B
------------------	--------

Electrical Data

Power supply	208-3-60
Unit min circuit ampacity	38.7 A
Unit max over-current protection	50 A

Dimensions & Weight

Hgt 50 in	Len 59 in	Wth 32 in
Weight with factory installed options	435 lb	

Clearances

Right	30 in	Front	36 in	Rear	24 in
Top	120 in	Bottom	0 in	Left	30 in

Note: Please refer to the tech guide for listed maximum static pressures



10 Ton

- Split System Units are Manufactured at an ISO 9001 Registered Facility.

Unit Features

- Two Stage Cooling
- Unit is designed for R454B refrigerant and is shipped with a small Nitrogen holding charge.
- Unit Cabinet Constructed of Powder Painted Steel, Certified At 750 Hours Salt Spray Test (ASTM B-117 Standards)
- Full Perimeter Base Rails with Built in Rigging Capabilities
- Scroll Compressors with Crankcase Heater
- Single Refrigeration Circuit (2 Pipe)
- Liquid Line Driers (Supplied for Field Installation)
- Aluminum Tube/ Aluminum Fin Microchannel Coils
- Back Seating Suction and Liquid Line Service Valves
- Inherently Protected Fan Motors
- Low Ambient to 40°F
- Side or Bottom Single Point Power Connections
- Short Circuit Current: 5kA RMS Symmetrical

Standard Unit Controller: Smart Equipment Control Board

- Anti-Short Cycle Protection, Lead-Lag, Low Voltage Protection, On-Board Diagnostic and Fault Code Display
- Safety Monitoring - Monitors the High and Low-Pressure Switches. The Unit Control Board will Alarm on Compressor Lockouts and Repeated Limit Switch Trips.

BAS Controller

- Smart Equipment Controller

Warranty

- One (1) Year Limited Warranty on All Other Parts
- Five (5) Year Limited Warranty on Compressors



OD Split System

Split-System Outdoor

Project Name: **454B Stock**

Unit Model #: **KC120C00A2AAA1**

Quantity: **1**

System: **KC120C00A2AAA1, GL120C00C2BAA1**

Additional Electrical Data

Power supply	208-3-60
Unit min circuit ampacity	38.7 A
Unit max over-current protection	50 A
Min Voltage	187 V
Max Voltage	252 V
Comp #1 RLA	26.5
Comp #1 LRA	255
Outdoor Mtr Qty	2
Outdoor Fan Voltage	208-1-60
OD Fan Mtr FLA (ea.)	2.8



OD Split System

Split-System Outdoor

Project Name: 454B Stock

Unit Model #: KC120C00A2AAA1

Quantity: 1

System: KC120C00A2AAA1, GL120C00C2BAA1

Factory Installed Options

KC120C00A2AAA1


Equipment Options		Option(s) Selected
Product Category:	K	Split System R-454B Air Conditioner
Product Identifier:	C	2-Pipe
Nominal Cooling Capacity:	120	10 Ton
Heat Type and Nominal Heat Capacity:	C00	
Airflow:	A	Standard Motor
Voltage:	2	208/230-3-60
Installation Options:	A	Smart Equipment Controller
Additional Options:	AA	
Product Generation:	1	

Project Name: 454B Stock

Unit Model #: KC120C00A2AAA1

Quantity: 1

Dimensions



Unit dimensions WE090, WC120, KE090, KC120, KC150

Unit height dimensions

MODEL	A
WE090	44.5
WC120	50.0
KE090	44.5
KC120	50.0
KC150	50.0

Piping and electrical connection sizes (in.)

Model	WE090	WC120	KE090	KC120	KC150
No. refrigeration circuits	1	1	1	1	1
Suction line OD (in.)	1 1/8	1 3/8	1 1/8	1 3/8	1 3/8
Liquid line OD (in.)	5/8	7/8	5/8	7/8	7/8
Power wiring knockout	1 3/8	1 3/8	1 3/8	1 3/8	1 3/8
Control wiring knockout	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8

Project Name: **454B Stock**

Unit Model #: **GL120C00C2BAA1**

Quantity: **1**

System: **KC120C00A2AAA1, GL120C00C2BAA1**

Supply Air Blower Performance

Supply air	4000 cfm
Ext. static pressure	0.6 IWG
Addl. Unit Losses (Options/Accessories)	0.05 IWG
Blower speed	804 rpm
Max BHP of Motor (including service factor)	2.30 HP
Duct location	Upflow
Motor rating	2.00 HP
Actual required BHP	1.65 HP
Power input	1.56 kW
Elevation	0 ft
Drive type	BELT

Indoor Electrical Data

Power supply	208-3-60
Unit min circuit ampacity	11.30 A
Unit max over-current protection	15 A


Indoor Dimensions & Weight

Hgt	65 in	Len	30 in	Wth	56 in
Weight with factory installed options	586 lb				

Indoor Clearances

Side w/Piping	24 in
Side Opposite Piping	24 in
Side w/ Return Air	24 in
Side w/ Supply Air	24 in

Note: Please refer to the tech guide for listed maximum static pressures



10 Ton

- Split system units are manufactured at an ISO 9001 registered facility

Unit Features

- Unit is designed for R454B refrigerant and is shipped with a small Nitrogen holding charge.
- Refrigerant Detection System is Factory Installed
- Unit Cabinet Constructed of Powder Painted Steel, Certified At 750 Hours Salt Spray Test (ASTM B-117 Standards).
- Easily converted in the field from vertical to horizontal configuration.
- Slide-out Composite Drain Pan
- Single Circuit Refrigeration
- Adjustable balanced port TXV's
- 2.0 HP Motor and Adjustable Sheave Belt Drive
- Unit ships with 2" Throwaway filters with a standard filter rack that will accept up to 4" filters.
- Short Circuit Current: 5kA RMS Symmetrical
- Intellispeed VFD w/o Bypass

Warranty

- One (1) Year Limited Warranty on all Other Parts
- Five (5) Year limited Warranty on Electric Heating Elements



ID Split System

Split-System Indoor

Page: 155

Project Name: **454B Stock**

Unit Model #: **GL120C00C2BAA1**

Quantity: **1**

System: **KC120C00A2AAA1, GL120C00C2BAA1**

Additional Electrical Data

Power supply	208-3-60
Unit min circuit ampacity	11.3 A
Unit max over-current protection	15 A
Min Voltage	187 V
Max Voltage	252 V
Indoor Mtr Voltage	208-3-60
Indoor Mtr FLA	9.0



ID Split System

Split-System Indoor

Project Name: 454B Stock

Unit Model #: GL120C00C2BAA1

Quantity: 1

System: KC120C00A2AAA1, GL120C00C2BAA1

Factory Installed Options

GL120C00C2BAA1

Equipment Options		Option(s) Selected
Product Category:	G	Split System R-454B Air Handler
Product Identifier:	L	2-pipe w/Intellispeed
Nominal Cooling Capacity:	120	10 Ton
Heat Type and Nominal Heat Capacity:	C00	
Airflow:	C	2.0 HP Motor
Voltage:	2	208/230-3-60
Installation Options:	B	Intellispeed VFD w/o Bypass
Additional Options:	AA	Composite Drain Pan
Product Generation:	1	

Project Name: 454B Stock

Unit Model #: GL120C00C2BAA1

Quantity: 1

Piping, Electrical & Duct Opening Connections

Piping, electrical and duct opening connection sizes

Model	GL090	GL120	GL180	GL240
System data				
No. Refrigeration Circuits	1	1	1	1
Suction Line OD (in.)	1 1/8	1 3/8	1 5/8	1 5/8
Liquid Line OD (in.)	5/8	7/8	7/8	7/8
Power Wiring Knockout	1 3/4	1 3/4	1 3/4	1 3/4
Control Wiring Knockout	1 1/8	1 1/8	1 1/8	1 1/8
Electric Heat Wiring Knockout	1 3/4	1 3/4	1 3/4	1 3/4
Drain Line Fitting PVC Stub	3/4	3/4	3/4	3/4
Blower outlet				
Number	1	1	1	2
Width	13.4	15.9	18.9	15.9
Length	15.6	18.6	21.6	18.6
Return air inlet				
Width	20.5	20.5	27.3	19.2
Length	52.0	52.0	71.9	93.4

Minimum clearances

Minimum Clearances	
Top with Supply Air Opening ¹	24 in.
Front with Return Air Opening	24 in.
Right Side with access for Piping, Power & Control Wiring Connections ²	36 in.
Left Side	24 in.
Rear ³	N/A
Bottom ⁴	N/A

¹ This dimension will vary if an electric heater, a supply air plenum or a base is used.

² This dimension is required for normal installation and service.

³ Although no clearance is required for service and operation, some clearance may be required for routing the power and control wiring.

⁴ Allow enough clearance to trap the condensate drain line.


Note: If the coil has to be removed, the blower section can be unbolted and set aside and the coil can be lifted out the top of the evaporator section.

Project Name: 454B Stock


Unit Model #: GL120C00C2BAA1

Quantity: 1


Typical Applications



Vertical Airflow Arrangements



Horizontal Airflow Arrangements





Project Name: 454B Stock



Unit Model #: GL120C00C2BAA1

Quantity: 1

Commercial Split Unit Dimensions



FRONT AND SIDE VIEW




Project Name: **454B Stock**

Unit Model #: **GL120C00C2BAA1**


Quantity: **1**

Dimensions 7.5 to 10 Ton P2

BOTTOM VIEW



HORIZONTAL CONFIGURATION



Electrical data for indoor models

Electrical data - evaporator units

Motor HP	Power Supply	Supply Blower Motor	Electric Heat Option				MCA ¹ (Amps)	Max Fuse ² / Breaker ³ Size (Amps)
		FLA	Model	KW	Stages	Amps		

GL/GM) 120 C00C (INTELLISPEED)								
2.0	208-3-60	9.0	None	---	---	---	11.3	15
			10 KW	7.5	1	20.8	37.3	40
			16 KW	12	2	33.4	52.9	60
			26 KW	19.5	2	54.2	78.9	80
			36 KW	27	2	75.1	104.9	110
	230-3-60	9.0	None	---	---	---	11.3	15
			10 KW	10	1	24.1	41.4	45
			16 KW	16	2	38.5	59.4	60
			26 KW	26	2	62.5	89.4	90
			36 KW	36	2	86.6	119.6	125
	460-3-60	4.6	None	---	---	---	5.8	15
			10 KW	10	1	12.0	20.8	25
			16 KW	16	2	19.2	29.8	30
			26 KW	26	2	31.3	44.9	45
			36 KW	36	2	43.3	59.9	60