

Project Name: cfm Distributors-York KJ150

Unit Model #: KJ150N24R2AAAAA1A1

Quantity: 1 Tag #: 14 ton horiz

System: KJ150N24R2AAAAA1A1

Cooling Performance

Total gross capacity	176.1 MBH
Sensible gross capacity	126.2 MBH
Efficiency (at ARI)	12.00 EER
Integrated eff. (at ARI)	15.20 IEER
Ambient DB temp.	95.0 °F
Entering DB temp.	80.0 °F
Entering WB temp.	67.0 °F
Evap Coil Leaving DB temp.	59.8 °F
Evap Coil Leaving WB temp.	57.4 °F
Unit Leaving DB temp.	62.2 °F
Unit Leaving WB temp.	58.3 °F
Leaving air temp dew point	55.9 °F
Power input (w/o blower)	11.20 kW
Sound power	82 dB(a)

Refrigerant

Refrigerant type	R-454B
Sys1	9 lb 6 oz
Sys2	8 lb 10 oz

Gas Heating Performance

Entering DB temp.	60 °F
Heating output capacity (Max)	194.0 MBH
Supply air	5800 cfm
Heating input capacity (Max)	240 MBH
Leaving DB temp.	91.0 °F
Air temp. rise	31.0 °F
SSE	81.0 %
Stages	2

Supply Air Blower Performance

Supply air	5800 cfm
Ext. static pressure	0.6 IWG
Blower speed	1133 rpm
Max BHP of Motor (including service factor)	5.75 HP
Duct location	Side
Motor rating	5.00 HP
Actual required BHP	4.57 HP
Power input	4.26 kW
Elevation	ft
Drive type	BELT

Electrical Data

Power supply	208-3-60	230-3-60
Unit min circuit ampacity	77.4 A	77.4 A
Unit max over-current protection	90 A	90 A

Dimensions & Weight

Hgt 51 in	Len 120 in	Wth 59 in
Weight with factory installed options		1395 lb

Clearances

Right	12 in	Front	48 in	Rear	12 in
Top	72 in	Bottom	0 in	Left	36 in

Note: Please refer to the tech guide for listed maximum static pressures



12.5 Ton

- York Sun Pro units are manufactured at an ISO 9001 registered facility and each rooftop is completely computer-run tested prior to shipment.

Product Features

- All units are manufactured at an ISO 9001 registered facility and each rooftop is completely computer-run tested prior to shipment.

Unit Features

- Refrigerant Detection System (RDS) is Factory Installed
- Two Stage Cooling
- 240 MBH Input Aluminized Steel, Two Stage Gas Heat
- Either supply and/or return can be field converted from vertical to horizontal configuration without cutting panels.
- Full perimeter base rails with built in rigging capabilities
- Unit Cabinet Constructed of Powder Painted Steel, Certified At 750 Hours Salt Spray Test (ASTM B-117 Standards)
- Scroll Compressor[s]
- Slide-Out Blower/5 HP Belt Drive Motor Assembly
- Unit Ships with 2" Throwaway Filters
- Solid Core Liquid Line Filter Driers
- Replacement Filters: 4 - (24" x 20").
- Single Point Power Connection
- Through-the-Curb and Through-the-Base Utility Connections
- Short Circuit Current: 5kA RMS Symmetrical
- Micro-Channel "all-aluminum" condenser coil, Copper tube/aluminum fin evaporator coil
- Composite Drain Pan - Front Connection
- Tool-free maintenance with features like hinged doors for all-access panels, slide-out blower and blower motor tray

BAS Controller

- IntelliSpeed control of the VFD based on stages of cooling. Provides Single Zone VAV Fan Operation as defined by ASHRAE 90.1 section 6.4.3.10.
- Smart Equipment Controller including Discharge Air, Return Air, and Outdoor Air Temperature Sensors.

Standard Unit Controller: Smart Equipment Control Board

- Safety Monitoring - Monitors the High and Low-Pressure Switches, the Freezestats, the Gas Valve, if Applicable, and the Temperature Limit Switch on Gas and Electric Heat Units. The Unit Control Board will Alarm on Ignition Failures, Safety Lockouts and Repeated Limit Switch Trips.

Warranty

- One (1) Year Limited Warranty on the Complete Unit
- Five (5) Year Warranty - Compressors and Electric Heater Elements
- Ten (10) Year Limited Warranty - Aluminized Steel Heat Exchanger



Project Name: cfm Distributors-York KJ150

Unit Model #: KJ150N24R2AAAAA1A1

Quantity: 1 Tag #: 14 ton horiz

System: KJ150N24R2AAAAA1A1

Additional Electrical Data

Power supply	208-3-60
Unit min circuit ampacity	77.4 A
Unit max over-current protection	90 A
Min Voltage	187 V
Max Voltage	252 V
Comp #1 RLA	22.4
Comp #1 LRA	166.2
Comp #2 RLA	22.4
Comp #2 LRA	166.2
Indoor Mtr Voltage	208-3-60
Indoor Mtr FLA	20.4
Outdoor Mtr Qty	4
Outdoor Fan Voltage	208-1-60
OD Fan Mtr FLA (ea.)	1.65
Power Ex Mtr Qty (if applicable)	1
Powered Ex Voltage(if applicable)	208-1-60
Power Ex Mtr FLA (ea) (if applicable)	5.5
Combustion Mtr Qty	1
Combustion Motor Voltage	208/230-1-60
Combustion Mtr FLA (ea)	0.5



Project Name: cfm Distributors-York KJ150

Unit Model #: KJ150N24R2AAAAA1A1

Quantity: 1 Tag #: 14 ton horiz

System: KJ150N24R2AAAAA1A1

Factory Installed Options

KJ150N24R2AAAAA1A1

Equipment Options		Option(s) Selected
Product Category :	KJ	Single Packaged R-454B Air Conditioner, High Efficiency 12.0 EER
Nominal Cooling Capacity :	150	12.5 Ton Two Stage Cooling
Heat Type and Nominal Heat Capacity :	N24	240 MBH Input Aluminized Steel, Two Stage Gas Heat
Blower Option :	R	5 HP High Static Belt Drive Blower IntelliSpeed control of the VFD based on stages of cooling (Provides Single Zone VAV Fan Operation as defined by ASHRAE 90.1 section 6.4.3.10)
Voltage :	2	208/230-3-60
Outside Air Option :	A	
Service Options :	A	Refrigerant Detection System
Sensor Options :	A	
Controls :	A	Smart Equipment Controller including Discharge Air, Return Air, and Outdoor Air Temperature Sensors.
Refrigeration :	A	Micro-Channel "all-aluminum" condenser coil, Copper tube/aluminum fin evaporator coil
Additional Options :	1	Standard 2" Throwaway Filters
Cabinet Options :	A	Composite Drain Pan - Front Connection Tool-free maintenance with features like hinged doors for all-access panels, slide-out blower and blower motor tray
Product Generation :	1	




3-12.5 York® Sun™ Pro

Project Name: cfm Distributors-York KJ150

Unit Model #: KJ150N24R2AAAAA1A1

Quantity: 1 Tag #: 14 ton horiz

Submittal



REV	DATE	DESCRIPTION	BY	CHK	ENG	SCALE	REVISION RECORD	THIRD ANGLE PROJECTION	ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER HEREOF ARE RESERVED AND NO PERMISSION IS GRANTED TO REPRODUCE THIS PRINT IN WHOLE OR IN PART OR TO DISCLOSE ANY OF THE CONTENTS HEREOF TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION BY YORK.	SAFETY AND KEY CHARACTERISTICS PER MATERIAL
A	10-31-23	NET DRAWING					100724 [LOP RCH BV]			TYPE NOT APPLICABLE
										EN SPEC NOT APPLICABLE
										SIZE
										PRO W COIL, 50" CAB
										JOHNSON CONTROLS
										UNITARY PRODUCTS GROUP
										NORMAN, OH 43069
										REV
										6454073
										PART NO.
										SHIT NO. 1 OF 1

Project Name: **cfm Distributors-York
KJ150**

Unit Model #: **KJ150N24R2AAAAA1A1**

Quantity: **1** Tag #: **14 ton horiz**

Component Locations

Cooling With Gas Heat (6.5 Through 10 Tons)

